SILVER AGM ULTRA

Product Data Sheet

SAMBA Code: 636 AGM

PUNCHED GRID | MATCHING QUALITY | VIBRATION RESISTANT | HIGH HEAT | SILVER (Ag) CALCIUM (Ca) | LONGER LIFE | FAST CHARGE | CYCLE LIFE

General	
Enertec Code:	22BAT636AGM-BLS
Technology:	Absorbed Glass Mat
Alloy:	Silver/Calcium
Maintenance:	Sealed Maintenance Free
Short Code:	636AGM-BLS
Charge Eye:	No

Electrical Specifications	
Voltage:	12 V
Capacity (20 hrs):	45 AH
CCA SAE (- 18°C):	430
CCA EN (0°C):	390

Dimensions / Mass	
Max Length (L):	237 mm
Max Width (W):	128 mm
Max Height (H):	199 mm
Total Height (TH):	220 mm
Mass (Weight):	13.0 kg

Transportation	
Classified as:	AGM Battery
Batteries, wet, non-spillable, electrical storage	
UN number:	UN 2800
Classification (ADR/RID)	Class 8
Packing Group	Not Assigned

Container	
Group Size:	B24 / NS60S
Case Material:	Polypropylene
Colour:	Grey
Bottom Hold Down:	B00
Terminal Type:	Tapered (1)
Layout:	RHP (0)

Terminal

01

Layout



Hold-down



B00

Drawings