


## SILVER AGM ULTRA

### Product Data Sheet

SAMBA Code: 674AGM

| General       |                         |
|---------------|-------------------------|
| Enertec Code: | 26BAT674AGM-BLS         |
| Technology:   | Absorbed Glass Mat      |
| Alloy:        | Silver/Calcium          |
| Maintenance:  | Sealed Maintenance Free |
| Short Code:   | 674AGM-BLS              |
| Charge Eye:   | No                      |




| Dimensions / Mass  |         |
|--------------------|---------|
| Max Length (L):    | 331 mm  |
| Max Width (W):     | 175 mm  |
| Height (H):        | 219 mm  |
| Total Height (TH): | 240 mm  |
| Mass (Weight):     | 26.2 kg |




| Electrical Specifications |       |
|---------------------------|-------|
| Voltage:                  | 12 V  |
| Capacity (20 hr):         | 90 AH |
| CCA SAE (-18°C):          | 940   |

| Container         |                |
|-------------------|----------------|
| Group Size:       | GR31           |
| Case Material:    | Polypropylene  |
| Colour:           | Grey           |
| Bottom Hold Down: | B00            |
| Terminal Type:    | Tapered (1)    |
| Layout:           | LHP Middle (7) |

| Transportation                                    |              |
|---|--------------|
| Classified as:                                    | AGM Battery  |
| Batteries, wet, non-spillable, electrical storage |              |
| UN number:  | UN 2800      |
| Classification (ADR/RID)                          | Class 8      |
| Packing Group                                     | Not Assigned |


| Terminal Type   | Layout  | Hold-Down  |
|---|---|--|
| <br>01 |  | <br>B00 |



PUNCHED  
GRID



MATCHING  
QUALITY



VIBRATION  
RESISTANT



HIGH  
HEAT



SILVER (Ag)  
CALCIUM (Ca)



LONGER  
LIFE



FAST  
CHARGE



CYCLE  
LIFE