ENERTEC NO LIMITS

BLUE SMF Premium

Product Data Sheet

SAMBA Code: 646



PUNCHED GRID | OE MATCHING QUALITY | VIBRATION RESISTANT | HIGH HEAT | SILVER (Ag) CALCIUM (Ca)

General	
Enertec Code:	20BAT646-BLC
Technology:	Sealed Flooded Battery
Alloy:	Lead Acid Calcium / Calcium
Maintenance:	Sealed Maintenance Free
Short Code:	646-BLC
Charge Eye:	Yes

Electrical Specifications	
Voltage:	12 V
Capacity (20 hrs):	55 AH
CCA SAE (- 18°C):	550
CCA EN (0°C):	510

Dimensions / Mass	
Max Length (L):	242 mm
Max Width (W):	175 mm
Max Height (H):	190 mm
Total Height (TH):	190 mm
Mass (Weight):	13.8 kg

Transportation	
Classified as:	Lead Acid
Batteries, wet, filled with acid, electrical storage	
UN number:	UN 2794
Classification (ADR/RID)	Class 8
Packing Group	Not Assigned


Container	
Group Size:	L2
Case Material:	Polypropylene
Colour:	Grey / Blue
Bottom Hold Down:	B13
Terminal Type:	Tapered (1)
Layout:	RHP (0)

Terminal



01

Layout



Hold-down



B13

Drawings

