SILVER SMF Premium PLUS

Product Data Sheet



PUNCHED GRID | MATCHING QUALITY | VIBRATION RESISTANT | HIGH HEAT | SILVER (Ag) CALCIUM (Ca) | LONGER LIFE

SAMBA Code: 638 HC

General	
Enertec Code:	22BAT638-BLS
Technology:	Sealed Flooded Battery
Alloy:	Lead Acid_Calcium / Calcium
Maintenance:	Sealed Maintenance Free
Short Code:	638-BLS
Charge Eye:	Yes


Electrical Specifications	
Voltage:	12 V
Capacity (20 hrs):	70 AH
CCA SAE (- 18°C):	550
CCA EN (0°C):	520

Dimensions / Mass	
Max Length (L):	256 mm
Max Width (W):	170 mm
Max Height (H):	203 mm
Total Height (TH):	225 mm
Mass (Weight):	16.9 kg

Transportation	
Classified as:	Lead Acid
Batteries, wet, filled with acid, electrical storage	
UN number:	UN 2794
Classification (ADR/RID)	Class 8
Packing Group	Not Assigned


Container	
Group Size:	D26R / NS70
Case Material:	Polypropylene
Colour:	Grey
Bottom Hold Down:	B00
Terminal Type:	Tapered (1)
Layout:	LHP (1)

Terminal




01

Layout



Hold-down



B00

Drawings

