SILVER AGM ULTRA

Product Data Sheet

SAMBA Code: 646AMG



PUNCHED GRID · MATCHING QUALITY · VIBRATION RESISTANT · HIGH HEAT · SILVER (Ag) CALCIUM (Ca) · LONGER LIFE · FAST CHARGE · CYCLE LIFE

General	
Enertec Code:	22BAT646AGM-BLS
Technology:	Absorbed Glass Mat
Alloy:	Calcium/Calcium
Maintenance:	Sealed Maintenance Free
Short Code:	646AGM-BLS
Charge Eye:	No


Electrical Specifications	
Voltage:	12 V
Capacity (20 hrs):	60 AH
CCA SAE (- 18°C):	700
CCA EN (0°C):	640

Dimensions / Mass	
Max Length (L):	242 mm
Max Width (W):	175 mm
Max Height (H):	190 mm
Total Height (TH):	190 mm
Mass (Weight):	17.2 kg


Transportation	
Classified as:	AGM Battery
Batteries, wet, non-spillable, electrical storage	
UN number:	UN 2800
Classification (ADR/RID)	Class 8
Packing Group	Not Assigned

Container	
Group Size:	L2
Case Material:	Polypropylene
Colour:	Grey
Bottom Hold Down:	B13
Terminal Type:	Tapered (1)
Layout:	RHP (0)

Terminal



Layout



Hold-down



Drawings

