SILVER SMF Premium PLUS

Product Data Sheet



PUNCHED GRID | MATCHING QUALITY | VIBRATION RESISTANT | HIGH HEAT | SILVER (Ag) CALCIUM (Ca) | LONGER LIFE

SAMBA Code: 650 HC

General	
Enertec Code:	22BAT650-BLS
Technology:	Sealed Flooded Battery
Alloy:	Lead Acid_Calcium / Calcium
Maintenance:	Sealed Maintenance Free
Short Code:	650-BLS
Charge Eye:	Yes


Electrical Specifications	
Voltage:	12 V
Capacity (20 hrs):	92AH
CCA SAE (- 18°C):	750
CCA EN (0°C):	680

Dimensions / Mass	
Max Length (L):	305 mm
Max Width (W):	171 mm
Max Height (H):	203 mm
Total Height (TH):	225 mm
Mass (Weight):	20.1 kg


Transportation	
Classified as:	Lead Acid
Batteries, wet, filled with acid, electrical storage	
UN number:	UN 2794
Classification (ADR/RID)	Class 8
Packing Group	Not Assigned

Container	
Group Size:	D31R
Case Material:	Polypropylene
Colour:	Grey
Bottom Hold Down:	B00
Terminal Type:	Tapered (1)
Layout:	LHP (1)


Terminal



Layout



Hold-down



B00

Drawings

