SILVER SMF Premium PLUS

Product Data Sheet



SAMBA Code: 659

General	
Enertec Code:	22BAT659-BLS
Technology:	Sealed Flooded Battery
Alloy:	Lead Acid_Calcium / Calcium
Maintenance:	Sealed Maintenance Free
Short Code:	659-BLC
Charge Eye:	Yes

PUNCHED GRID | OE MATCHING QUALITY | VIBRATION RESISTANT | HIGH HEAT | SILVER (Ag) CALCIUM (Ca) | LONGER LIFE


Electrical Specifications	
Voltage:	12 V
Capacity (20 hrs):	85 AH
CCA SAE (- 18°C):	780
CCA EN (0°C):	740

Dimensions / Mass	
Max Length (L):	315 mm
Max Width (W):	175 mm
Max Height (H):	175 mm
Total Height (TH):	175 mm
Mass (Weight):	19.1 kg

Transportation	
Classified as:	Lead Acid
Batteries, wet, filled with acid, electrical storage	
UN number:	UN 2794
Classification (ADR/RID)	Class 8
Packing Group	Not Assigned


Container	
Group Size:	LB4
Case Material:	Polypropylene
Colour:	Grey
Bottom Hold Down:	B13
Terminal Type:	Tapered (1)
Layout:	RHP (0)

Terminal



01

Layout



Hold-down



B13

Drawings

