ENERTEC NO LIMITS.®

SILVER SMF Premium PLUS

Product Data Sheet

SAMBA Code: 695



PUNCHED GRID | MATCHING QUALITY | VIBRATION RESISTANT | HIGH HEAT | SILVER (Ag) CALCIUM (Ca) | LONGER LIFE

General	
Enertec Code:	26BAT695-BLS
Technology:	Sealed Flooded Battery
Alloy:	Lead Acid_Calcium / Calcium
Maintenance:	Sealed Maintenance Free
Short Code:	695-BLS
Charge Eye:	Yes


Electrical Specifications	
Voltage:	12 V
Capacity (20 hrs):	225 AH
CCA SAE (- 18°C):	1300
CCA EN (0°C):	1200

Dimensions / Mass	
Max Length (L):	516 mm
Max Width (W):	275 mm
Max Height (H):	217mm
Total Height (TH):	242mm
Mass (Weight):	54.5kg

Transportation	
Classified as:	Lead Acid
Batteries, wet, filled with acid, electrical storage	
UN number:	UN 2794
Classification (ADR/RID)	Class 8
Packing Group	Not Assigned

Container	
Group Size:	Typ C / N225
Case Material:	Polypropylene
Colour:	Grey
Bottom Hold Down:	B00
Terminal Type:	Tapered (1)
Layout:	LHP (3)

Terminal




01

Layout



Hold-down



B00

Drawings

