

GOLD SMF UPS

Product Data Sheet

Short Code: 1150

General

Enertec Code:	20BUG-1150-BLG
Technology:	Wet_Sealed Maintenance Free
Alloy:	Silver/Calcium
Maintenance:	Sealed Maintenance Free
Short Code:	1150-BLG
Charge Eye:	Yes

Electrical Specifications

Voltage:	12 V
Capacity (20 hrs):	100 AH

Test Specifications

CCA SAE (- 18°C):	860
-------------------	-----

Transportation

Classified as:	Lead Acid
Batteries, wet, filled with acid, electrical storage	
UN number:	UN 2794
Classification (ADR/RID)	Class 8
Packing Group	Not Assigned



LONGER LIFE



PUNCHED GRID



HIGH HEAT



SILVER (Ag)
CALCIUM (Ca)


Dimensions / Mass

Max Length (L):	330 mm
Max Width (W):	172 mm
Max Height (H):	219 mm
Total Height (TH):	242 mm
Mass (Weight):	24.5 kg

Container

Group Size:	G31
Case Material:	Polypropylene
Colour:	Black
Bottom Hold Down:	B00
Terminal Type:	Threaded Stud (13)
Layout:	LHP Middle (7)

Terminal



13

Layout



Hold-down



B00

Drawings

