

GOLD SMF UPS

Product Data Sheet

Short Code: NS70L

General

Enertec Code:	20BUG-NS70L-BLG
Technology:	Wet_Sealed Maintenance Free
Alloy:	Silver/Calcium
Maintenance:	Sealed Maintenance Free
Short Code:	NS70L-BLG
Charge Eye:	Yes

Electrical Specifications

Voltage:	12 V
Capacity (20 hrs):	70 AH

Test Specifications

CCA SAE (- 18°C):	550
-------------------	-----

Transportation

Classified as:	Lead Acid
Batteries, wet, filled with acid, electrical storage	
UN number:	UN 2794
Classification (ADR/RID)	Class 8
Packing Group	Not Assigned

Dimensions / Mass

Max Length (L):	256 mm
Max Width (W):	173 mm
Max Height (H):	203 mm
Total Height (TH):	225 mm
Mass (Weight):	16.9 kg

Container

Group Size:	D26L / NS70L
Case Material:	Polypropylene
Colour:	Grey
Bottom Hold Down:	B02
Terminal Type:	Tapered (1)
Layout:	RHP (0)



LONGER LIFE



PUNCHED GRID



HIGH HEAT




SILVER (Ag)
CALCIUM (Ca)

Terminal



01

Layout



Hold-down



B02

Drawings

